KSTRONG UNRIVALED SAFETY.

ECOR

ENERGY ABSORBING ADJUSTABLE WEBBING LANYARD

TECHNICAL DATA SHEET



KStrong has developed a range of Shock Absorbing Adjustable Webbing Lanyards to ensure the user is protected when working at heights. The shock absorber effectively arrests the fall, minimising the forces to the body.

KSTRONG®
UNRIVALED SAFETY.

ECOR

ENERGY ABSORBING ADJUSTABLE 44MM WEBBING LANYARD



Energy Absorbing Adjustable Webbing Lanyard C/W Snap Hooks

ANL408131(AD)



Energy Absorbing Adjustable Webbing Lanyard C/W Snap & Scaffold Hook

ANL408141(AD)



Energy Absorbing Adjustable Webbing Twin Leg Lanyard C/W Snap & Scaffold Hooks

ANL408612(AD)

KSTRONG®
UNRIVALED SAFETY.

ECOR

ENERGY ABSORBING ADJUSTABLE WEBBING LANYARD

LANYARD CODES			
FEATURES	ANL408131(AD)	ANL408141(AD)	ANL408612(AD)
WEIGHT			
	1170gm	1414gm	2288gm
FEATURES			
44MM WEBBING	✔	✔	✔
SNAP HOOK	✔	✔	✔
SCAFFOLD HOOK		✔	✔
LABEL PACK	✔	✔	✔
ENERGY ABSORBER	✔	✔	✔
COMPASS ASSET TECHNOLOGY	✔	✔	✔
LENGTH IN METERS			
	2m	2m	2m
CAPACITY			
	140kg	140kg	140kg
RELEVANT STANDARDS			
AS 1891.5:2020	✔	✔	✔

10 Year Shelf Life From Date Of Manufacture.

KSTRONG®
UNRIVALED SAFETY.

ECOR

ENERGY ABSORBING ADJUSTABLE WEBBING LANYARD

MATERIAL SPECIFICATIONS

WEBBING

- Polyester 44mm wide
- MBS 25kN

THREAD / STITCHING

- High Tenacity Polyester (Colour Contrasted)

METAL COMPONENTS

- ANSI Steel Snap Hooks - MBS 23kN
- ANSI Scaffold Hook Steel - MBS 23kN
- Finish - Silver Galvanized

ENERGY ABSORBER

- 44mm Polyester Back Up Webbing
- 44mm Polyamide Tear Webbing
- Protective Covering