

# D-Ring Anchor with Anchorage Plate

The D-ring anchor with anchorage plate offers a compact, reliable connection point for your fall protection system that may be attached to the structure using fasteners or weld.



**Model No.:**  
2101630

**Dimensions:**

- Anchorage Plate - H = 6.35mm, W = 50mm, L = 115mm
- D-ring - Internal Diameter = 57mm, External width = 84mm, Height = 107mm

**Weight (approx):**  
0.5kg

**Materials:**

- D-ring - forged alloy steel
- Anchorage Plate - stainless steel

**Mounting Requirements:**

- Hole size - 14mm
- Fasteners - M12 Set Screw/Bolt
- Welding - welded in accordance with the latest codes and specifications. Must be welded by qualified welder
- The anchor point must be installed to structure that is capable of withstanding Anchor Point Loads.

Note: If there are any concerns about integrity of structure, it shall be investigated by an engineer.

- All mounting holes must be a 13mm clearance hole and must not be within 25mm from an edge on a steel beam.

**Capacity:**

One User - 136kg

**Rating:**

22kN

**Compatibility:**

DBI-SALA anchors are designed for use with DBI-SALA approved components or systems, or as recommended by a competent person.

**Standards:**

AS/NZS 1891.4

**Country of Origin:**

U.S.A.

**Special Instructions/Conditions of Use:**

- Reading user instruction manual prior to use is essential.
- To be installed by a competent person
- Annual inspection & re-certification is required as per AS/NZS 1891.4.



Capital Safety - Australia & New Zealand  
 Australia: 1800 245 002 | New Zealand: 0800 212 505  
[www.capitalsafety.com.au](http://www.capitalsafety.com.au)  
[sales@capitalsafety.com.au](mailto:sales@capitalsafety.com.au)

• Asia: +65 6558 7758    • Latin America: +1 651 385 4301  
 • USA: 800.328.6146    • Northern Europe: +44 (0) 1928 571234  
 • Canada: 800 387 7484    • Germany: +49 2634 8052  
 • Europe, Middle East, Africa: +33 (0)4 97 10 00 10

