

REBEL™ PERSONAL
SELF RETRACTING LIFELINES

ECONOMICAL

DEPENDABLE

SAFE

With Rebel™ Personal Self Retracting Lifelines (SRL's) you get an economical fall protection solution in a compact unit that minimises your fall clearance requirements when working at height.

Rebel SRL's don't compromise on safety and continue to set performance standards beyond compliance, while providing substantial value compared to competitive models.



REBEL™ PERSONAL SELF RETRACTING LIFELINES

Rebel™ Personal SRL Models

FEATURES AND BENEFITS

TOP SWIVEL

Limits lifeline twisting and improves user experience.

TRIPLE OR DOUBLE ACTION KARABINER

For easy connection to anchorage point or harness (triple action karabiner on 1.8 m model only)

HEAT-SHRUNK

Clear PVC coating over label and shock pack/fall indicator for improved durability, added protective Kevlar® fibre cover on Hot Work model

IMPACT RESISTANT

Thermoplastic housing – lightweight, compact and durable

HIGH STRENGTH

Thin webbing or galvanised cable for Hot Work provides added durability and longevity

16 kN GATE HOOKS

High capacity, reduces the risks of accidental disengagement (roll-out), swivel impact indicating hook on Hot Work cable model

140 KG CAPACITY

Meets a wide range of user weights



3100445
1.8 m Web SRL

3100447
3.3 m Web SRL

3100448
6 m Web SRL

3590025
4.5 m Cable SRL

Still using a lanyard?
The 1.8 m Rebel™ Personal SRL is the perfect way to upgrade



Other Rebel™ SRL Products



Rebel™ cable SRL range available in 6, 10, 15, 20 & 30 metre models. View separate product sheet for more information.

SPECIFICATIONS	Webbing Lifeline Models			Cable Lifeline Model
Part Number	3100445	3100447	3100448	3590025
Length	1.8 m	3.3 m	6.0 m	4.5 m
Weight	1.3 kg	1.6 kg	2.5 kg	3.1 kg
Anchorage Connector	Karabiner, steel, triple action, 19 mm gate opening, 16 kN gate	Karabiner, steel, double action, 18 mm gate opening, 16 kN gate	Karabiner, steel, double action, 18 mm gate opening, 16 kN gate	Karabiner, steel, double action, 18 mm gate opening, 16 kN gate
Lifeline Termination	Snap hook, steel, double action, 19 mm gate opening, 16 kN gate	Snap hook, steel, double action, 19 mm gate opening, 16 kN gate	Snap hook, steel, double action, 19 mm gate opening, 16 kN gate	Snap hook with swivel & fall indicator, steel, double action 19 mm gate opening, 16 kN gate
Components	Housing: Nylon, UV resistant; Drum: Nylon, Type 6/6; Fasteners: Stainless steel screws and rivets; Locking Pawls: Stainless steel; Main Shaft: Stainless steel; Motor Spring: Carbon steel; Swivel: Zinc plated steel; Lifeline: Webbing - 25 mm polyester web, Cable - 7 x 19 galvanised steel cable; Energy Absorber: Webbing Model - Polyester with PVC tubing cover, Cable model - polyester web with Kevlar® fibre cover			
Arresting Force/Distance	Average Arresting Force = 4 kN Maximum Arresting Force = 6 kN Maximum Arresting Distance = 0.6 m (when anchored overhead)			
Capacity	140 kg			
Standards	Meets EN 360 and AS/NZS 1891.3			
Compatibility	Rebel SRL's are compatible for use with all Capital Safety approved components and systems, or as recommended by a competent person			
Country of Origin	U.S.A.			
Special Instructions/Conditions of Use	Reading User Instruction Manual prior to use is essential. Rebel Personal SRL's are not designed for foot-level tie-off			

Kevlar® is a registered trademark of E.I. du Pont de Nemours and Company



Capital Safety™

Australia: 1800 245 002 | New Zealand: 0800 212 505
www.capitalsafety.com.au sales@capitalsafety.com.au



FOR MORE INFORMATION
VISIT US AT
CAPITALSAFETY.COM.AU

