

WHEN YOUR LIFE IS ON THE LINE, DEPEND ON)-LINFTM

Ultimate Job Site Versatility

The PRO-Line™ temporary horizontal lifeline system is lightweight, easy to install and extremely portable, Just disassemble and take to the next job. The PRO-LineTM system will work alongside you during maintenance, bridge work, construction and manufacturing with absolute safety and reliability.

versatile

to lifeline

18m Webbing Lifeline

Floating Connection O Rings

Provides a secure and

strong connection of your

personal fall arrest system

Compact, portable and

Fast and Easy Installation

The PRO-Line™ system installs in seconds without special tools or equipment, maintaining optimum worker productivity. Simply attach the lifeline and tie-off adaptors to 22kN rated anchorage points and tension the lifeline with the integrated ratchet. The system is extremely lightweight and portable, allowing you to move it and reuse it over and over again. Refer to the user instruction manual for complete operating details including required clearance distances.

Complete Worker Confidence

The built-in shock absorber limits arresting forces during a fall and provides the user with a visual impact indicator for added safety. Connection to the lifeline is made by attaching the hook of a shock absorbing lanyard directly to the lifeline for complete ease-of-use. The carrying bag makes transporting and storing the system easy, reduces damage from dirt, moisture and UV degradation thus improving the longevity of the system. Reliability that saves you worry, time and money.

Complete System

A complete temporary horizontal lifeline in a convenient carry

Integral Tensioner Built-in tensioner for fast set up and removal PROTECTA **Built-in Shock Absorber**

Reduces anchorage loadings to preserve structure

Karabiner End Terminations Allows for easy connections to tie-off Tie-Off Adaptors adaptors For simple anchorage to structure

1200101 - PRO-Line™ Temporary Horizontal Lifeline System

kit includes:

- 18m Lifeline with integral tensioner, shock absorber, karabiner end terminations and two floating connection O rings
- Two 1.8m tie-off adaptors
- Equipment kit bag.

Specifications:

Lifeline Webbing: 50mm Polyester, 50kN tensile strength. Tie-Off Adaptor Webbing: 44mm Polyester Strength Member with 75mm Wear Pad. Hardware: Zinc Plated Alloy Steel, 22kN tensile strength. Ratchet: Zinc plated steel, 22kN tensile strength. Weight (approx.): 6kg (aprprox). Capacity: Rated to 22kN, for two users, end connectors must be rated to 22kN. *Compatibility:* Protecta PRO-Line™ is designed for use with all Capital Safety approved components and systems, or as recommended by a competent person. Standards: Complies to AS/NZS1891.2. Country of Origin: Canada Special Instructions/Conditions of Use: Reading user instruction manual prior to use is essential.



Capital Safety - Australia & New Zealand Australia: 1800 245 002 | New Zealand: 0800 212 505 www.capitalsafety.com.au sales@capitalsafety.com.au

- Asia: +65 6558 7758
- Latin America: +1 651 385 4301
- **USA:** 800.328.6146
- Northern Europe: +44 (0) 1928 571234
- Canada: 800 387 7484Germany: +49 2634 8052
- Europe, Middle East, Africa: +33 (0)4 97 10 00 10

