

DELTA™ KEEPS IMPROVING BECAUSE SAFETY NEVER GETS OLD.



DURABLE, COMFORTABLE & SAFE

Continuing a tradition of cutting-edge research and design, the **DELTA™** full body harness range provides a series of enhanced features to deliver absolute safety, comfort and peace of mind.



NEW FEATURES, SAME DEPENDABLE RELIABILITY

Ideal for use by telecommunications and power industry personnel when working on towers and poles.

DELTA™ TOWER WORKERS HARNESS

Features:

- Large rear fall arrest rated spring loaded stand-up D-ring for fast, easy and safe connections to fall protection system
- Frontal fall arrest/belay loops
- Corrosion resistant hardware for harsh work environments
- Quick-connect buckles on legs, chest and waist for fast connections ensuring an exact fit every time
- Confined space/retrieval attachment points for raising and lowering
- Waist belt with side angled D-rings for climbing and work positioning
- Wide padded lower back/hip pad for added support and comfort
- Padded work positioning buttock seat with D-rings for pole work
- REPEL™ Technology Webbing construction, repels liquids, naturally self-cleaning and enhances durability
- Rip stitch impact Indicator, allows the user to quickly and easily inspect the harness for impact loading
- Easy grip end tabs and keepers for fast efficient and secure web adjustment
- Fully adjustable shoulder, chest, waist and leg straps, for a perfect fit every time
- Clearly labelled/identifiable attachment points
- Labels with permanent indent print conveniently located in a single location and safeguarded by a unique cover protecting vital information - donning instructions, harness data, inspection log, product certification and i-Safe™ tag
- Colour coded sizing for easy identification
- Sub pelvic strap for added security
- Exclusive no-tangle design holds the shape of the harness providing added comfort and ease of donning
- Anti roll-out design - designed to minimise the risk of roll-out when connecting a DBI-SALA lanyard or SRL with either double locking hooks, Capital Safety patented trigger action hooks or karabiners to a large fall arrest rated D-ring
- i-Safe™ enabled to track inspections, control inventory and manage information
- Bonus harness storage bag ensures your DELTA™ harness is kept free from damage when not in use
- Available in Small, Medium, Large and Extra Large sizes
- Certified and approved to AS/NZS 1891.1



853S0018 | Small

853M0018 | Medium

853L0018 | Large

853XL0018 | Extra Large

Specifications:

Colour: Yellow. **Webbing:** REPEL™ technology webbing - 45mm, minimum breaking load 15kN, resistant to UV and common organic solvents (if in doubt contact manufacturer). **Thread:** polyester. **Hardware:** Rear stand-up D-ring - Fall arrest rated, drop forged steel, minimum break strength 20kN, internal diameter width - 56mm; Frontal Fall Arrest Loops - REPEL™ technology webbing, minimum breaking load 15kN; Side D-Rings - Drop forged steel, minimum break strength 20kN, internal diameter width - 45mm; Pole/Restraint D-rings - Drop forged steel, minimum break strength 20kN, internal diameter width - 56mm; Quick-Connect Buckles - Chest, waist & legs, solid riveted construction, steel; Shoulder adjusters - Spring loaded, steel zinc plated. **Delta® Back Pad:** Polyethylene and vinyl acetate. **Lower Back & Buttock Seat Pads:** Inner layer - high density foam, outer layer - nylon. **Weight (approx):** 2.80kg. **Temperature (working environment):** -20°C to 50°C (guide only). **Capacity:** 136kg, combined weight of person, tools, clothing etc (160kg when used with a DBI-SALA Lanyard manufactured from the 1/08/2008). **Compatibility:** DBI-SALA harnesses are designed for use with DBI-SALA approved components or systems, or as recommended by a competent person. **Standards:** AS/NZS 1891.1:2007. **Country of Origin:** Australia. **Special Instructions/Conditions of Use:** Reading user instruction manual prior to use is essential. If a dorsal extension is part of your harness the maximum lanyard assembly permitted is 1.7m or less.



Capital Safety - Australia & New Zealand
Australia: 1800 245 002 | New Zealand: 0800 212 505
www.capitalsafety.com.au
sales@capitalsafety.com.au

