

ELIMINATING THE SHOCK FACTOR FOR SAFE & SECURE CONNECTIONS.



ELIMINATING THE SHOCK FACTOR FOR SAFE & SECURE CONNECTIONS

Ideal for Fall Arrest, Work Positioning and Restraint

DBI-SALA shock absorbing lanyards combine strength and ease of use providing a safe and secure means of connecting your fall protection harness to a secure anchorage point. They are designed to quickly and effectively arrest a fall, whilst minimising shock loads on the body.

EZ-STOP™ SHOCK ABSORBING LANYARDS RANGE



Z8-69-69

Z90203636

Z51200934

Z51203636

Z51204545



Z90203634E



Z90203636E



Z60203634E



Z20203636



ZP67110204560X

FEATURES

- General purpose fall arrest lanyard suitable for fall arrest, work positioning and restraint
- Minimises shock loads on the body limiting the arresting forces to under 6kN in the event of a fall
- Elasticated models reduce trip fall hazards, dragging and catching for complete freedom of movement
- Adjustable lanyards allow the user to have a shorter tie-off point, and minimise free fall/work positioning distance, adjusts from 750mm to 2 metres in length
- Double tail style lanyards helps you remain connected at all times
- Constructed from heavy duty 45mm polyester grey webbing or 11mm kernmantle rope for durability and longevity
- Shock absorbing unit encased in UV resistant transparent plastic for easy inspection
- Lanyard and shock pack stitching visible for easy inspection
- Protected labels for durability and longevity
- Rated to 160kg - ideal for all workers regardless of shape, size and weight
- i-Safe™ enabled to track inspections, control inventory and manage information
- Ideal for use in all kinds of industrial environments and applications

NOTE: For a wider variety of shock absorbing lanyards refer to our Force2™ lanyard range.

Specifications:

Part Number	Connectors		Length	Weight (Approx.)	Tails	Flat Webbing	Elasticated Webbing	Adjustable	Rope
	Harness	Anchorage							
Z8-69-69	R-105-S-CE	R-105-S-CE	300mm	0.85kg	Single				
Z90203636	9503319	9503319	2m	1.30kg	Single	✓			
Z51200934	9502116	07153	2m	1.10kg	Single	✓		✓	
Z51203636	9503319	9503319	2m	1.10kg	Single	✓		✓	
Z51204545	R-119	R-119	2m	1.15kg	Single	✓		✓	
Z90203634E	9503319	07153	2m	1.05kg	Single		✓		
Z90203636E	9503319	9503319	2m	1.40kg	Single		✓		
Z60203634E	9503319	07153	2m	2.20kg	Twin		✓		
Z20203636	9503319	9503319	2m	1.25kg	Single				✓
ZP67110204560X	R-119	H031 & R-119	2m	1.60kg	Single			✓	✓

Webbing: Polyester webbing - 45mm. **Kernmantle Rope:** 11mm diameter, Minimum tensile strength - 25kN, polyester cover, braided over a nylon core, low stretch, torque-balance. **Thread:** Polyester. **Adjuster Webbing Models:** Spring loaded, Fall arrest rated drop forged steel. **Adjuster Rope Model:** Manual rope adjuster, Steel. **Connectors:** Refer to separate product information sheets. **Capacity:** 50-160kg (combined weight of person, tools, clothing, etc.). **Minimum Breaking Strength:** 15kN. **Activation:** Activates at a minimum force of 200kg. **Maximum Arresting Force:** Impact force on user is kept below 6kN (in the event of a fall). **Lanyard Extension:** In the event of a fall lanyard may extend an additional length of 1.75m. **Compatibility:** Designed for use with Capital Safety approved harnesses, components or systems, or as recommended by a competent person.

Standards: AS/NZS 1891.1. **Country of Origin:** Australia. **Special Instructions/Conditions of Use:** Reading user instruction manual prior to use is essential. If a dorsal extension is part of your harness the maximum lanyard assembly permitted is 1.7m or less.



Capital Safety™ - Australia & New Zealand
Australia: 1800 245 002 | New Zealand: 0800 212 505
www.capitalsafety.com.au
sales@capitalsafety.com.au

