

Temporary Tie-Off Adaptor Range

Product description

Temporary Anchorage connectors are a great way to quickly and easily set up a temporary anchorage for connection by a lanyard or fall arrest device. Light-weight and easy to trans- port, these tie-off adaptors range from a simple webbing loop to a wire tie-off for specific applications. All tie-off adaptors are suitable for single person fall arrest applications.

FEATURES

Webbing Tie-Off adaptors

- Webbing tie-off
- Made from 25mm Day-Glo webbing
- Ultimate tensile strength (UTS) > 20kN
- For single person use
- Available in 1 metre & 2 metre versions

Cross Arm Slings

- Anchorage strap with large and small alloy d-ring at each end.
- Chokes through itself around a suitable anchorage point.
- Provides easy attachment to small alloy d-ring by lanyard.
- For single person use only.
- 750kg WLL (600kg in choke)
- Available in 1 metre & 2 metre versions

APPLICATIONS

- Construction
- Maintenance
- Roofing
- Most work at height applications.

Ordering Details

PART NO.	DESCRIPTION	LENGTH	MIN QTY	CAT	PACKAGE DIMENSIONS	WEIGHT	BARCODE
WTO1M	Webbing tie-off	1m	1	A	180 x 50 x 30	128g	9333633003508
WTO2M	Webbing tie-off	2m	1	A	210 x 70 x 30	236g	9333633003515
CAS1	Cross arm sling	1m	1	A	210 x 110 x 80	633g	9333633001689
CAS2	Cross arm sling	2m	1	A	210 x 140 x 90	1.1kg	9333633001696
ME1009	Dee reversed eye	1m	1	A	220 x 70 x 70	349g	N/A
PCL1	Plastic coated wire tie-off	1m	1	A	280 x 250 x 20	262g	9333633003072
PCL2	Plastic coated wire tie-off	2m	1	A	280 x 250 x 20	380g	9333633003089

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM HONEYWELL SAFETY PRODUCTS AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL SAFETY PRODUCTS RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Honeywell Safety Products Australia Pty Ltd

Australia 1300 139 166
New Zealand 0800 322 200
www.honeywellsafety.com

Cross Arm Sling



Plastic Coated Wire Tie Off



Webbing Tie Off



Dee Reversed Eye Tie Off



Technical Information

Dee Reversed Eye tie-off

- 1m anchorage strap with d-ring one end and reversed eye on other.
- Protective sleeve prevents wear on webbing.
- Easy attachment to d-ring by lanyard or anchorage line.

Plastic coated wire tie-off

- 6mm plastic coated galvanised wire.
- Thimble eyes each end.
- Suited for use over sharp edges or in welding environments.

Standards

Refer to AS/NZS 1891.4 for information on anchorage strength, position and other application guidelines.