

# Miller® Sharp Edge Scorpion™ Fall Arrestor

## Product description

When working at height a sharp edge is an especially challenging environment both for equipment and for people. The light-weight, compact design of the Sharp Edge Scorpion Fall Arrestor provides workers with an effective fall protection solution when working near Sharp Edges.

The Sharp Edge Scorpions are compliant to the Sharp Edge Test featured in the European Standard and provides workers ultimate protection should a fall take place over a sharp edge. The Sharp Edge Scorpions feature a quick action braking system that arrests fall within centimetres. Compact and light these sharp edge tested retractable lifelines must be attached to the rear D-Ring of the harness with the energy absorber end when working near sharp edges. Extremely solid and light the Scorpion retractable lifelines contain internal components that are corrosion resistant comprising an Aluminium and Stainless Steel casing and shock-resistant thermoplastic housing.

## FEATURES

- Compact and light-weight
- Quick activating high strength stainless steel braking system - arrests free fall within centimeters
- No annual factory recertification required
- Complete with 25mm Polyamide sharp edge rated webbing
- Corrosion resistance internal components. Stainless Steel / Aluminium body encased in a high impact polymer cover.
- The sharp edge scorpions can be used in horizontal applications however the shock absorber MUST be attached to the back D-ring of the harness when using the units horizontally.

## APPLICATIONS

- Any general work at height application
- Construction and maintenance.

## Ordering Details


PART NO.	DESCRIPTION	TERMINATIONS	LENGTHS	MIN QTY	CAT	PACKAGE DIMENSIONS	WEIGHT	BARCODE
1016840	Sharp edge rated scorpion	Steel screw-gate karabiner & snap hook	2.6m	1	A	265 x 170 x 90	1.9kg	3660681041333
1016841	Sharp edge rated scorpion	Alum screw-gate karabiner & scaff hook	2.7m	1	A	265 x 170 x 90	1.9kg	3660681041340

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM HONEYWELL SAFETY PRODUCTS AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL SAFETY PRODUCTS RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

## Honeywell Safety Products Australia Pty Ltd

Australia 1300 139 166  
New Zealand 0800 322 200  
[www.honeywellsafety.com](http://www.honeywellsafety.com)

Doc | Rev | 09/16  
© 2016 Honeywell Safety Products Australia Pty Ltd



## Technical Information

Housing:	Thermoplastic/Aluminium
Brake:	Stainless Steel
Webbing:	Polyamide 25mm
Overall Length:	Please refer table below
Working Length:	2.2m
Length retracted:	750mm
E/A Deployment:	300mm
Swivel hook:	Please refer table below
Max. working load:	140kg
Max. Arresting force:	4kN

## Standards

Certified to Australian and New Zealand Standards AS/NZS 1891.3