



PRO Riggers Full-Body  
Harness With Integral Lanyard

# Total Compliance, Absolute Confidence.

Re-designed and upgraded to provide optimum safety and comfort for everyday use by professionals in a broad range of industry applications.



3M Science. Applied to Life.™

# 3M™ Protecta® PRO Riggers Full-Body Harness With Integral Lanyard

Full-body harnesses are genuine working tools that allow you to get on with your job without worrying about safety. That's why our all new re-designed and upgraded 3M™ Protecta® PRO Full-Body Harness Range offers a choice of harnesses for every possible working environment, from general construction to tower work. With a design that incorporates lighter hardware and improved adjustability for a perfect fit every time, they ensure absolute confidence, comfort and safety for the user, making them a great value safety solution.

The *PRO Riggers Full-Body Harness With Adjustable Integral Lanyard* is ideal for rigging, rescue, construction, elevated work platforms, ladder access work, roof work and general height safety.

## Features:

**Front fall arrest rated D-ring**, Ideal for climbing, work positioning or rescue.

**Large rear fall arrest rated D-ring with adjustable integral lanyard**, for fast, easy and safe connections to your fall protection system. (models available with scaffold or snap hook).

**Adjustable integral lanyard**, adjusts from 750 mm to 2 m in length allowing the user to easily adjust the length of the lanyard to control free fall/work positioning distance to suit their work environment.

**Pass-thru buckles on chest and leg straps**, provides quick and easy donning and adjustments.

**Easy adjust torso buckles**, simple and fast pull down adjustment buckles for a perfect fit every time.

**Retrieval attachment points**, for raising and lowering in rescue and confined space applications.

**Lightweight hardware and components**, reduces weight and user fatigue.

**Polyester webbing**, for superior abrasion resistance and durability.

**Protected Labels**, labels with permanent indent print conveniently located in a single location and safeguarded by a unique cover protecting important information.

**Sub pelvic strap**, for extra protection.

**Flexible sizing**, available in small, medium, large and extra large.

**Custom harness label (optional)**, have your harness customised with your company logo for easy identification and personalisation.

**Bonus harness storage bag**, ensures your PRO harness is kept free from damage when not in use.

**Certified and approved**, conforms to AS/NZS 1891.1.



Optional Custom Harness Label  
Minimum order quantity applies

### Scaffold Hook Model

Part No.	Size
AB126-34S	Small
AB126-34M	Medium
AB126-34L	Large
AB126-34XL	Extra Large

### Snap Hook Model

Part No.	Size
AB126-36S	Small
AB126-36M	Medium
AB126-36L	Large
AB126-36XL	Extra Large

Note: Also available with elasticated integral lanyard.

View the complete PRO Full-Body Harness Range at [www.3M.com.au/FallProtection](http://www.3M.com.au/FallProtection)

**Specifications:** Colour: Red and grey. **Webbing:** 45 mm Polyester, minimum breaking load 15 kN, resistant to UV and common organic solvents (if in doubt contact manufacturer). **Thread:** Polyester. **Hardware:** Rear D-ring - Fall arrest rated, high tensile steel, clear zinc finish, minimum tensile strength 22.2 kN, internal diameter width 56 mm; Frontal D-ring - Fall arrest rated, high tensile steel, clear zinc finish, minimum tensile strength 22.2 kN, internal diameter width 45 mm; Buckles - Chest and legs, pass-thru style, high tensile steel, clear zinc finish; Torso Adjusters - 2 bar/2 bar, high tensile steel, clear zinc finish. **Lanyard:** Adjuster - fall arrest rated drop forged steel; Connectors - snap hook (2000161) or scaffold hook (2000164), drop forged steel, clear zinc finish, 16 kN rated gate; Activation - activates at a minimum force of 200 kg; Maximum Arresting Force - impact force on user is kept below 6 kN (in the event of a fall); Lanyard Extension - in the event of a fall lanyard may extend an additional length of 1.75 m. **Weight (approx.):** Scaffold hook model - 2.4 kg, Snap hook model - 2.0 kg (based on medium size). **Capacity:** 136 kg, combined weight of person, tools, clothing, etc. (160 kg when used with a Protecta lanyard manufactured from the 1/08/2008). **Compatibility:** Protecta harnesses are designed for use with Protecta approved components or systems, or as recommended by a competent person. **Standards:** AS/NZS 1891.1. **Country of Origin:** Australia. **Special Instructions/Conditions of Use:** Reading user instruction manual prior to use is essential.



**3M Fall Protection Business**  
Personal Safety Division  
95 Derby Street  
Silverwater, NSW, 2128, Australia

Australia: 1800 245 002  
New Zealand: 0800 212 505  
[www.3M.com.au/FallProtection](http://www.3M.com.au/FallProtection)  
[sales@capitalsafety.com.au](mailto:sales@capitalsafety.com.au)

