**DELTA**<sup>™</sup> RIGGERS COMFORT HARNESS

DELTA KEEPS IMPROVING BECAUSE SAFETY NEVER GETS OLD.



**DURABLE, COMFORTABLE & SAFE** 

Continuing a tradition of cutting-edge research and design, the **DELTA™** full body harness range provides a series of enhanced features to deliver absolute safety, comfort and peace of mind.



## NEW FEATURES, SAME DEPENDABLE RELIABILITY

Ideal for use in rigging, confined space, ladder access and general height safety.

## DELTA™ RIGGERS COMFORT HARNESS

## Features:

- Lightweight aluminium hardware for reduced weight and greater comfort
- Large rear fall arrest rated D-ring for fast, easy and safe connections to fall protection system
- Fall arrest rated frontal D-ring for work positioning or rescue
- Corrosion resistant hardware for harsh work environments
- Quick-connect buckles on legs and chest for fast connections ensuring an exact fit every time
- Easy-adjust torso buckles for fast and easy adjustments
- Lightweight dual density foam/aerospace mesh comfort padding on shoulders, back and legs provides a durable lightweight moisture wicking and breathable padding
- Confined space/retrieval attachment points for raising and lowering
- Lanyard keepers provide the ideal storage solution for unanchored lanyard tails
  whilst working at height for ease of access and safety and break away to avoid a
  trip hazard
- REPEL<sup>TM</sup> Technology Webbing construction, repels liquids, naturally self-cleaning and enhances durability
- Rip stitch impact Indicator, allows the user to quickly and easily inspect the harness for impact loading
- Easy grip end tabs and keepers for fast efficient and secure web adjustment
- Fully adjustable shoulder, chest and leg straps, for a perfect fit every time
- Clearly labelled/identifiable attachment points
- Labels with permanent indent print conveniently located in a single location and safeguarded by a unique cover protecting vital information donning instructions, harness data, inspection log, product certification and i-Safe<sup>TM</sup> tag
- Colour coded sizing for easy identification
- Sub pelvic strap for added security
- Exclusive no-tangle design holds the shape of the harness providing added comfort and ease of donning
- Anti roll-out design designed to minimise the risk of roll-out when connecting a DBI-SALA® lanyard or SRL with either double locking hooks, Capital Safety patented trigger action hooks or karabiners to a large fall arrest rated D-ring
- i-Safe<sup>TM</sup> enabled to track inspections, control inventory and manage information
- Bonus harness storage bag ensures your DELTA™ harness is kept free from damage when not in use
- Available in Small, Medium, Large and Extra Large sizes
- $\bullet$  Certified and approved to AS/NZS 1891.1

 833S2018
 | Small
 833M2018
 | Medium

 833L2018
 | Large
 833XL2018
 | Extra Large





## Specifications:

Colour: Yellow/Blue. Webbing: REPELTM technology webbing - 45 mm, minimum breaking load 15 kN, resistant to UV and common organic solvents (if in doubt contact manufacturer). Thread: polyester. Hardware: Rear D-ring - Fall arrest rated, aluminium, minimum break strength 22.2 kN, internal diameter width - 59 mm; Front D-ring - Fall arrest rated, aluminium, minimum break strength 22.2 kN, internal diameter width - 51 mm; Quick-Connect Buckles - Chest & legs, solid riveted construction, aluminium; Shoulder adjusters - Spring loaded, aluminium. Comfort Padding: Aerospace mesh, EVA foam, nylon mesh. Weight (approx): 1.5 kg. Temperature (working environment): -20°C to 50°C (guide only). Capacity: 136 kg, combined weight of person, tools, clothing etc (160 kg when used with a DBI-SALA Lanyard manufactured from the 1/08/2008). Compatibility: DBI-SALA harnesses are designed for use with DBI-SALA approved components or systems, or as recommended by a competent person. Standards: AS/NZS 1891.1. Country of Origin: Australia. Special Instructions/Conditions of Use: Reading user instruction manual prior to use is essential. If a dorsal extension is part of your harness the maximum lanyard assembly permitted is 1.7m or less.



Capital Safety™ - Australia & New Zealand Australia: 1800 245 002 I New Zealand: 0800 212 505 www.capitalsafety.com.au sales@capitalsafety.com.au





