

# Data sheet

# SKYSAFE PRO FLEX Y



## **GENERAL**

Art. no.: L-AUS-0595-1,8 E-class number: 40-02-01-04

EAN: 4030281186878 Customs no.: 56090000



## Data sheet

## SKYSAFE PRO FLEX Y

ONE4ALL - The SKYSAFE PRO

Revolutionary, new energy absorber with the large weight range from 50 - 140kg (110 - 310 lbs.) that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m (5.7 Feet).

The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO furthermore meets the most relevant international standards in one SINGLE product.

UNIQUE: The built-in, adjustable RESCUE LOOPS! As a result, rescuers need not set up a rescue system and hereby save precious time in a rescue!

Available in four versions with different carabiner combinations:

I-web, Y-web, I-web tie-back, Y-web tie-back.

### **GENERAL**

Internat. standard: AS/NZS 1891.1:2007

#### **FEATURES**

#### Fall indicator

i ali iridicator	
Breaking load, major axis:	
50,00 kN	
Hand-washing:	40 °C
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons	: 1
Rated load:	140 KG
Rescue Loop:	yes
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND



### **DIMENSIONS**

 Size:
 1,8m

 Weight:
 2,75 kg

HARDWARE

Carabiner on anchoring point side:

FS 90 ST ANSI

Carabiner on belt side: SNAP HOOK 23kN

**MATERIAL** 

Material: Polyester, Steel

Webbing material: Polyester