

Data sheet

BEAMTAC 2.0



GENERAL

| | |
|-----------|------------------------------------|
| Art. no.: | AP-075 |
| EAN: | 4030281263388 |
| Standard: | CEN/TS 16415:2017 EN 795/B:2012 |

| | |
|-----------------|-------------|
| E-class number: | 40-02-01-90 |
| Customs no.: | 76169990 |

Data sheet

BEAMTAC 2.0

The BEAMTAC 2.0 mobile anchoring device is suitable for use as an attachment clamp for steel beams with a flange width of 90 to 380 millimetres and can be used for many different kinds of work in an industrial environment. The successor to the popular BEAMTAC is impressive thanks to its ergonomically optimised operating elements and safety benefits. The easily adjustable clamping jaws ensure rapid and simple attachment to steel beams, whilst the multi-level safety system reliably prevents any unwanted movement or slipping during use.

BEAMTAC 2.0 - essential for work in steel and industrial construction, as well as for all other types of plants with a suitable structure (steel beams).

GENERAL

Internet only:

| | |
|---------------------|------------------------|
| Internat. standard: | ANSI/ASSE Z359.18-2017 |
|---------------------|------------------------|

FEATURES

| | |
|--------------------|----------|
| Max. service life: | 10 Years |
|--------------------|----------|

| | |
|-------------------------|---|
| Max. number of persons: | 1 |
|-------------------------|---|

Area of application:

Construction / Roofer / Carpenter, Lift
Construction, Rope Access / Rigging

DIMENSIONS

| | |
|-------|------------------|
| Size: | 490 x 75 x 109mm |
|-------|------------------|

| | |
|---------|---------|
| Weight: | 1,99 kg |
|---------|---------|

MATERIAL

| | |
|-----------|-----------|
| Material: | Aluminium |
|-----------|-----------|