

Data sheet
BFD FLEX



GENERAL

Art. no.: L-AUS-0403-2
EAN: 4030281162438

E-class number: 40-02-01-04
Customs no.: 56090000

Data sheet

BFD FLEX

The elasticised webbing single leg BFD Personal Energy Absorbing range reduces the overall length of the lanyard by 73cm (2mt version), 40cm (1,5mt version) or 25cm (1.2mt version) and are all designed to effectively arrest a fall whilst minimising the shock loads on the body. The 'Tear Tape' technology shock pack utilises a controlled tearing action that is initiated when the lanyard is 'loaded' during the fall and limits the fall arrest forces to below 6kN. The shock pack features a unique Velcro attach cover that provide 100% inspection as well as the potential to clean & dry the pack contents if necessary. The cover is also designed to protect the label pack, conveniently sewn into the tear tape material.

GENERAL

Internat. standard:	AS/NZS 1891.1:2007
---------------------	--------------------

FEATURES

Colour:	black / white
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND

DIMENSIONS

Size:	2m
Weight:	1,18 kg

HARDWARE

Carabiner on anchoring point side:	SNAP HOOK 23kN
Carabiner on belt side:	SNAP HOOK 23kN

MATERIAL

Material:

Polyester, Polyamide, Steel

Webbing material: Polyester, Polyamide
