

ANCHOR-TO-GO

TEMPORARY SHEET METAL ROOF ANCHOR

AAP000M

Simple and effective for roof access onto sheet metal roofs. Fits to edge of the roof sheeting (in the gutter line) with simple cam clamps to hold in place. By attaching a ropeline and throwing the rope to the opposite side of the roof, it means workers can access the roof area and add other fall arrest anchorages on the upper roof area as required.

RATING: 15kN

LIFESPAN: 10 Years

CERTIFICATION:



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
AAP000M		3700g	49 x 50cm	Powder coated steel	15kN

PRODUCT FEATURES

- Fall arrest rated for one person.
- Does not require any fixings.
- Only suitable for sheet metal roofing with a minimum of 0.42m thickness. Use only on roofing which is sound and well fixed.
- Essential anchor for a worker that needs to access rooftops such as plumbers, servicing technicians, installers, painters.

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA
 10 Holt Place,
 Harewood, Christchurch 8053
 New Zealand
 sales.nz@zeroheightsafety.com

EUROPE & UK
 Badenerstrasse 122
 5466 Kaiserstuhl,
 Switzerland
 sales.eu@zeroheightsafety.com

