

## MULTIBEAM

MULTI ANGLE I-BEAM ANCHOR

### AMB00XM

Temporary anchorage point for both horizontal and vertical use. To be used in conjunction with a fall arrest system and shock absorbing lanyard or a self retracting lifeline for fall arrest or with a positioning lanyard for fall restraint. Clamps to any beam flange for both horizontal and vertical use, the flange can be located on the top, bottom (horizontal) or side (vertical) of an I-Beam which has a minimum width of 125mm and maximum width of 300mm.



**RATING:** 15kN

**LIFESPAN:** 10 Years

**CERTIFICATION:** EN795:1996

EN 795:2012 Personal fall protection equipment. Anchor devices



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
		4700g	440 x 100 x 45mm	Steel & Aluminium Alloy	15kN

### PRODUCT FEATURES

- Do not use for material handling.
- Click lock action for best fit, with locator points to secure once clamped.

#### ZERO HEIGHT SAFETY LIMITED

**AUSTRALASIA**  
10 Holt Place,  
Harewood, Christchurch 8053  
New Zealand  
sales.nz@zeroheightsafety.com

**EUROPE & UK**  
Badenerstrasse 122  
5466 Kaiserstuhl,  
Switzerland  
sales.eu@zeroheightsafety.com