

Delta Plus Twin Lanyard (Elastic Webbing) with Energy Absorber

This Lanyard is suitable for use as a complete personal fall protection system. The Lanyard provides a connection between the users harness and an anchor. See AS/NZS 1891.4 for selection use and maintenance of suitable fall protection equipment.



Standard

- ▲ Certified to AS1891.5:2020

Material Specification

- ▲ Webbing & Thread: Polyester
- ▲ Hardware: High Tensile Steel, Zinc Plated
- ▲ Label: Vinyl

- ▲ Minimum User Capacity: 50kg
- ▲ Minimum Fall Clearance: 5.4m
- ▲ Maximum User Capacity: 150kg
- ▲ Minimum Fall Clearance: 6.6m
- ▲ Lifespan from manufacturing: 10 years
- ▲ Colour: Black/Orange



www.safetylink.com



Catalogue



Safety Centre
Training

Product Code	Harness Connector	Anchor Connector	Single or Twin	Leg Material	WEIGHT (KG)
WAUAN245200JWW	Snap Hook	Rebar Hook	Twin	Elastic	2.40

Always consult the instructions provided by the manufacturer of each component of your fall arrest system to accurately assess Fall Clearance.

Free-fall shall never exceed 2m.

Maintenance

The Lanyard shall be inspected before and after each use by the user. The Lanyard is not serviceable. Once the item fails inspection, is involved in a fall or if the remove from service date is reached (10 years from date of manufacturer for AS 1891.5 products) it shall be removed from service and destroyed to prevent use.

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-7883 Version: 3.0