

# TETHA T BAR & V BAR: TEMPORARY ANCHOR PLATES

PART CODE: **HSTBS280** | **HSTBS500** | **HSRTBA**



## PRODUCT INFORMATION >

The LINQ Tetha Roof T Bar and V Bar temporary anchor plates are engineered for extreme workplace situations.

Boasting a minimum breaking strength of 15kN, the range has been developed to be a durable and efficient temporary roof line anchor system. (It is important to ensure that the structure to which any LINQ Tetha anchor plate is installed, has sufficient strength (refer to ASNZS 1891.4) to sustain the applied load.)

## PRODUCT FEATURES >

- Can withstand fall arrest forces up to 15kN (It is important to ensure that the structure to which any LINQ Tetha anchor plate is installed, has sufficient strength (refer to ASNZS 1891.4) to sustain the roof applied load).
- The Tetha T-Bar has an easy to use camlock, no fixing required.
- Install within seconds
- Can be used as a temporary anchor point in applications along a roof line where no permanent anchor point exists.
- Quick installation and removal. (Installation should always be conducted by a competent person as described in ASNZS 1891.4).

## TECHNICAL INFORMATION >

- **High Strength Alloy Steel:** Ultimate Breaking Strength 15kN (Min.).
- **VITAL TEST COMPLIANCE:** Static Strength: 15kN for 3 minutes Dynamic Performance: Maximum breaking force does not exceed 6kN in the line when tested on a free falling mass of 100 kgs with the use of LINQ shock absorber pack.

## WARNING >

- For use on metal clad roof only.
- Refer to product user guide for safe use instructions.

## STANDARDS >

Conforms to ASNZS 1891.4 requirements.

Conforms to ASNZS 5532:2013 (NOTE the ultimate strength is directly related to the strength of the structure to which the LINQ Tetha anchor plate is installed, it is prudent practice to ensure that structure strength meets criteria and in assessing this it is recommended that the opinion of a qualified person (e.g. a structural engineer) is obtained.

Passed the corrosion test in accordance with ISO 9227:1990 – 24 hours. LINQ conducts testing over a 48 hour period.

## ANCHOR TETHA T-BAR HSRTBA

- Suitable for Fall Arrest application on metal roofs. To be used on metal clad roofs only.



## ANCHOR TETHA V-BAR STRAIGHT 280MM HSTBS280

- Provides safe 360° work area
- For use on metal roofs.
- 280mm size all purpose metal roofs.



## ANCHOR TETHA V-BAR STRAIGHT 500MM HSTBS500

- Provides safe 360° work area.
- For use on metal roofs.
- 500mm used for Trimdeck or Custom Orb roofs.

