

V-SHOCK Self-Retracting Devices

Data Sheet



Material Specifications	
WEIGHT	See tables
UNIT LENGTH	
1.8 m	1.83 m
2.5 m	2.55 m
6 m	6.10 m
10 m	10.06 m
15 m	15.24 m
UNIT WIDTH	
SINGLE-LEG PFL	119 mm to 144 mm
TWIN-LEG PFL	237 mm to 288 mm
6 m SRL	203.20 mm
10 m SRL	260.35 mm
15 m SRL	260.35 mm
UNIT DEPTH	
1.8 m PFL	66.55 mm
2.5 m PFL	68.07 mm
6 m SRL	101.60 mm
10 m SRL	114.30 mm
15 m SRL	114.30 mm
HOUSING MATERIAL	Nylon
HARDWARE MATERIALS	Steel or Aluminum
LIFELINE MATERIAL	
LEADING EDGE WEB PFL	25.4 mm wide/3.6 mm thick HMPE/ para aramid blend
LEADING EDGE CABLE SRL	5.5 mm diameter galvanized steel cable
ENERGY ABSORBING TECHNOLOGY	Tear Tape



*V-SHOCK Edge
Leading Edge PFLs*



*V-SHOCK Edge
Leading Edge SRLs*

V-SHOCK Self-Retracting Devices

Data Sheet



Specifications & Ordering Information

V-SHOCK Edge Leading Edge Galvanized Steel Cable SRL				
Part Number	Type	Length	Snaphook	Item Weight
VSLEG-061-NE-E	V-SHOCK Edge	6 m	36CS	4.67 kg
VSLEG-101-NE-E	V-SHOCK Edge	10 m	36CS	7.76 kg
VSLEG-151-NE-E	V-SHOCK Edge	15 m	36CS	8.39 kg

V-SHOCK Edge 1.8 m Leading Edge Web PFL				
Part Number	Type	Single/Twin	Snaphook	Item Weight
VSLEW-011-PC-E	V-SHOCK Edge	Single	ALTAKS	1.75 kg
VSLEW-011-PE-E	V-SHOCK Edge	Single	36CS	2.05 kg
VSLEW-011-PM-E	V-SHOCK Edge	Single	36CLS	2.17 kg
VSLEW-011-PH-E	V-SHOCK Edge	Single	AL36CLS	2.25 kg
VSLEW-012-PC-E	V-SHOCK Edge	Twin	ALTAKS	3.08 kg
VSLEW-012-PE-E	V-SHOCK Edge	Twin	36CS	3.68 kg
VSLEW-012-PM-E	V-SHOCK Edge	Twin	36CLS	3.94 kg
VSLEW-012-PH-E	V-SHOCK Edge	Twin	AL36CLS	4.09 kg

V-SHOCK Edge 2.5 m Leading Edge Web PFL				
Part Number	Type	Single/Twin	Snaphook	Item Weight
VSLEW-021-PC-E	V-SHOCK Edge	Single	ALTAKS	2.11 kg
VSLEW-021-PE-E	V-SHOCK Edge	Single	36CS	2.41 kg
VSLEW-021-PM-E	V-SHOCK Edge	Single	36CLS	2.54 kg
VSLEW-021-PH-E	V-SHOCK Edge	Single	AL36CLS	2.61 kg
VSLEW-022-PM-E	V-SHOCK Edge	Twin	36CLS	4.89 kg
VSLEW-022-PH-E	V-SHOCK Edge	Twin	AL36CLS	5.04 kg



Connectors

36CS Steel 21 mm Gate	36CLS Steel 50 mm Gate
ALTAKS Aluminium triple lock 19 mm Gate	AL36CLS Aluminium 60 mm Gate
Locking Pin Connector	

Performance Specifications	
STANDARDS & CAPACITY*	
EN 360	60-141 kg
DIN 19427	
MAXIMUM ARREST FORCES	
PEAK	470 kg
AVERAGE	366 kg



MSA—The Safety Company

Established in 1914, MSA Safety Incorporated is the global leader in the development, manufacture, and supply of safety products that protect people and facility infrastructures. Many MSA products integrate a combination of electronics, mechanical systems, and advanced materials to protect users against hazardous or life-threatening situations. The company's comprehensive product line is used by workers around the world in a broad range of markets, including the oil, gas, and petrochemical industry, the fire service, the construction industry, mining, and the military. MSA's core products include self-contained breathing apparatus, fixed gas and flame detection systems, portable gas detection instruments, industrial head protection products, firefighter helmets and protective apparel, and fall protection devices. With 2021 revenues of \$1.4 billion, MSA employs approximately 4,800 people worldwide. The company is headquartered north of Pittsburgh in Cranberry Township, PA, and has manufacturing operations in the United States, Europe, Asia, and Latin America. With more than 40 international locations, MSA realizes approximately half of its revenue from outside North America. For more information visit MSA's web site at www.MSAafety.com.

Our Mission

MSA's mission is to see to it that men and women may work in safety and that they, their families, and their communities may live in health throughout the world.

MSA: WE KNOW WHAT'S AT STAKE.

MSA Australia

11 Columbia Way
Norwest Business Park
BAULKHAM HILLS NSW 2153
PO Box 7325
Phone: 61 2 9688 0333
Customer Service: 1300 728 672
Fax: (02) 9896 1835
E-mail: aus.customerservice@MSAafety.com

MSA New Zealand

Customer Service: 0800 441 335
E-mail: nz.customerservice@MSAafety.com

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit <https://us.msafety.com/Trademarks>.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit MSAafety.com/offices.