

## DATASHEET SKYSAFE PRO+



## **GENERAL**

L-AUS-0836-1C8
4030281310167
40-21-08-10
56090000

Standards:	AS 1891.5:2020
Net weight:	2.48 kg
Gross weight:	2.48 kg



## DATASHEET SKYSAFE PRO+

The SKYSAFE PRO+ is a lanyard with flexible arms and ultra-compact shock absorber that covers a weight range from 50 to 150 kg and reduces the force to less than 6 kN with a maximum fall arrest distance of 1.75 m. In the event of a fall, the sewn-in RESCUE LOOPS allow the casualty to be lifted with a rescue device, relieving the load on the carabiner and facilitating rescue. Available in four different versions with different carabiner combinations.

- · Compact shock absorber for high freedom of movement
- Universally applicable thanks to wide weight range from 50 to 150 kg
   Quick and easy rescue thanks to integrated RESCUE LOOPs

## **FEATURES**

Application areas:	Wind energy, Off Shore Industry, Mobile Work Platforms, Scaffolding, lithium_ion, Elevator construction
Colour:	Black
Fallindicator:	Yes
Impact force:	6.00 kN
Hand wash:	30 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Rescue loop:	Yes
Lanyard type:	Y-Version
DIMENSIONS	
Rope length:	1.80 m
length_lanyard:	1.80 m
Lanyard rope diameter:	30.00 mm
MATERIAL	
Material:	Polyester