



### TUFF-BLOC-PRO

6 METRES  
PRODUCT CODE: TUFF-BLOC-PRO006

10 METRES  
PRODUCT CODE: TUFF-BLOC-PRO010

15 METRES  
PRODUCT CODE: TUFF-BLOC-PRO015

20 METRES  
PRODUCT CODE: TUFF-BLOC-PRO020



### TUFF-BLOC-EDGE (Coming Soon)

6 METRES  
PRODUCT CODE: TUFF-BLOC-EDGE006

10 METRES  
PRODUCT CODE: TUFF-BLOC-EDGE010

15 METRES  
PRODUCT CODE: TUFF-BLOC-EDGE015

20 METRES  
PRODUCT CODE: TUFF-BLOC-EDGE020

The SafetyLink Tuff-Bloc is a Self Retracting Lifeline suitable for use as part of a personal fall protection system. Non edge rated versions of the Tuff-Bloc Pro shall be used in the vertical or near vertical orientation. The Tuff-Bloc Edge models can be used horizontally and shall be used if there is a chance a fall occurring over a leading edge. Where possible the Tuff-Bloc should be used to limit free fall to less than 600mm (2ft).



SCAN ME

safetylink.com



SCAN ME

Catalogue



SCAN ME

Safety Centre  
Training

### Standard

The Tuff-Bloc Pro models listed in Figure 1 are certified to;

**EN360-2002** 40-140kg  
**AS/NZS 1891.3-2020** 40-140kg  
**ANSI Z359.14-2021** 130-310lbs Class 1  
**CSA Z259.2.2-17** 130-310 lbs  
**OSHA 1910.140** 420lbs

The Tuff-Bloc Edge models listed in Figure 1 are certified to;

**EN360-2002 and RFU 11.060** 40-140kg  
**AS/NZS 1891.3-2020** 40-140kg  
EU Declaration can be found at <https://www.safetylink.com>

### User Rating

The Tuff-Bloc is rated for one user.

***If a fall could occur over an edge, ensure an edge rated model is used.***

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on [ip@safetylink.com](mailto:ip@safetylink.com) and quote the product code.




Doc ID: MKT-8007 Version: 2.0

### Anchor

When selecting an anchor for use with the Tuff-Bloc Self Retracting Lifeline, consider the local standards and regulations. Where a free fall does not exceed 600mm (2ft), the anchor selected shall be rated to a minimum of 12kN (2700lbs). Where a free fall can exceed 600mm (2ft), the anchor selected shall be rated to 15kN (3400lbs).

**For leading edge applications, the anchor shall not be located below the edge.**

**The fall hazard shall never be between the user and the anchor when using this product.**

|    | Product Code      | Anchor Below Connection /Edge Rated | Functional Length | Retracted Length (A) | Width (B)        | Thickness (C)    | Weight             |
|---|-------------------|-------------------------------------|-------------------|----------------------|------------------|------------------|--------------------|
|   | TUFF-BLOC-PRO006  | <input type="checkbox"/>            | 6m<br>(20ft)      | 610mm<br>(24")       | 226mm<br>(8.9")  | 86mm<br>(3.4")   | 3.5kg<br>(7.7lbs)  |
|   | TUFF-BLOC-PRO010  | <input type="checkbox"/>            | 10m<br>(33ft)     | 610mm<br>(24")       | 226mm<br>(8.9")  | 86mm<br>(3.4")   | 4.4kg<br>(9.8lbs)  |
|   | TUFF-BLOC-PRO015  | <input type="checkbox"/>            | 15m<br>(50ft)     | 671mm<br>(26.4")     | 259mm<br>(10.2") | 97.5mm<br>(3.8") | 6.8kg<br>(15lbs)   |
|   | TUFF-BLOC-PRO020  | <input type="checkbox"/>            | 20m<br>(66ft)     | 701mm<br>(27.6")     | 292mm<br>(11.5") | 99mm<br>(3.9")   | 9.1kg<br>(20.1lbs) |
|  | TUFF-BLOC-EDGE006 | <input checked="" type="checkbox"/> | 6m<br>(20ft)      | 860mm<br>(33.9")     | 226mm<br>(8.9")  | 86mm<br>(3.4")   | 4.0kg<br>(8.8lbs)  |
|   | TUFF-BLOC-EDGE010 | <input checked="" type="checkbox"/> | 10m<br>(33ft)     | 860mm<br>(33.9")     | 226mm<br>(8.9")  | 86mm<br>(3.4")   | 4.7kg<br>(10.4lbs) |
|   | TUFF-BLOC-EDGE015 | <input checked="" type="checkbox"/> | 15m<br>(50ft)     | 920mm<br>(36.2")     | 259mm<br>(10.2") | 97.5mm<br>(3.8") | 7.1kg<br>(15.7lbs) |
|   | TUFF-BLOC-EDGE020 | <input checked="" type="checkbox"/> | 20m<br>(66ft)     | 950mm<br>(37.4")     | 292mm<br>(11.5") | 99mm<br>(3.9")   | 9.4kg<br>(20.7lbs) |

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on [ip@safetylink.com](mailto:ip@safetylink.com) and quote the product code.

Doc ID: MKT-8007 Version: 2.0